## AMENDMENT NO. 1 DECEMBER 2016 TO

## IS 12417 : 1988 SPECIFICATION FOR SUCTION APPARATUS, PEDAL OPERATED

(Page 1, clause 3.4, line 3) — Substitute "IS 3624: 1987 'Pressure and vacuum gauges (second revision)' for 'IS 3624: 1979\*'."

(Page 1, footnote \*) — Delete.

(Page 2, clause 3.8.1, sentence 3) — Substitute the following for the existing sentence:

"It shall conform to Type A of IS 5680: 1969 'Rubber tubing for medical use'."

(*Page* 2, footnote \*) — Delete.

(*Page* 2, *clause* **5.2**) — Substitute the following for the existing clause:

"5.2 The components made from brass shall be plated chromium over nickel in accordance with Service Condition 2 of IS 1068: 1993 'Electroplated coatings of nickel plus chromium and copper plus nickel plus chromium — Specification (third revision)'."

(*Page* 2, *clause* **5.3**) — Substitute the following for the existing clause:

"5.3 The components made from mild steel or cast iron shall be either plated chromium over nickel in accordance with Service Condition 2 of IS 1068: 1993 'Electroplated coatings of nickel plus chromium and copper plus nickel plus chromium – Specification (*third revision*)' or shall be painted in accordance with the procedure given in 5.3.1 to 5.3.3."

(*Page* 2, *clause* **5.3.2**) — Substitute the following for the existing:

"5.3.2 After pickling, all components shall be given phosphate treatment in accordance with IS 3618: 1966 'Phosphate treatment of iron and steel for protection against corrosion' followed by a coating of suitable primer conforming to IS 2074: 1992 'Ready mixed paint, air drying, red oxide, zinc chrome priming — Specification (second revision)', for air drying process and IS 2075: 2005 'Ready mixed paint, stoving, red oxide, zinc chrome priming —

## Amendment No. 1 to IS 12417: 1988

Specification (second revision)' for stove process. Filler shall be applied to all surfaces requiring filling."

[Page 2, clause **5.3.3** b)]— Substitute the following for the existing clause:

"b) Finish coat with synthetic stoving enamel shall conform to IS 150: 1950 'Specification for ready mixed paint, brushing, finishing, stoving, for enamel, colour as required'."

(Page 2, All footnotes) — Delete.